

Stressless®

LILLY

A plush, soft chenille with lasting durability and comfort.

Celebrated for its softness and luxurious texture, Lilly is a tightly woven, textured fabric with a small, grid like weave. This chenille material has a textural mix of matt and subtle sheen and offers durability with a plush feel. Produced in Turkey, utilizing a high percentage of recycled materials, Lilly is a sustainable choice with a sumptuous and contemporary weave. Available in shades that will complement any decor. It works well on all our furniture and is a robust choice that is simple to maintain and will stand the test of time.

ABRASION (MARTINDALE)	
(Hard wear domestic use 25.000)	60.000
PILLING 4-5	scala 1-5
LIGHT FASTNESS 5	scala 1-8
COLOUR FASTNESS DRY 4-5	scala 1-5
COLOUR FASTNESS WET 4-5	scala 1-5
CIGARETTE TEST	pass

Composition: 94% polypropylene,
6% polyester – recycled fibres in polypropylene

Price group: 3



Maintenance and cleaning

Fabrics made from synthetic fibres such as polyester, polyamide and acryl have a unique wear resistance, long durability and good light fastness. To help the surface retain its appearance, we recommend vacuuming the furniture regularly and wipe the surface with a damp cloth as needed. Remove spills immediately. If stains and dirt cannot easily be removed with a damp cloth, a cleaning agent and stain remover from the Stressless® Fabric Care Kit may be used.

Fabrics

We are uncompromising when it comes to fabric quality, and we cooperate with suppliers that manufacture in accordance with strict quality and environmental requirements. If correctly maintained, the fabrics we have selected will help give the furniture a long life. All our upholstery fabrics meet and exceeds the requirements of mobelfakta.no for Hard Wear. To meet Hard Wear requirements, the fabric must pass international tests for durability, light fastness, pilling resistance, fire safety and colour fastness. Tested in accordance with ISO 105-B02 (Light fastness) EN-12947-2, Martindale (wear test), and with ISO 12945-2 (pilling) and ISO 105x12 (rubbing/dye, wet and dry) and EN 1021-1 (Fire safety test).



EASY CARE



MORE RESPONSIBLE
FABRICS

High proportion of
recycled material



Read more
about our fabrics